

GRIND NUMBER
ENGINE IDENT. 1957 - 1987 CHEVROLET V - 8 262 THRU 400 CU. IN.

VALVE SETTING: INTAKE .000		EXHAUST .000		HOT
LIFT: INTAKE @ CAM 3254		@ VALVE 488		ROCKER ARM RATIO
EXHAUST @ CAM 3254		@ VALVE 488		1.5
ALL LIFTS ARE BASED ON ZERO LASH AND THEORETICAL ROCKER ARM RATIOS				
CAM TIMING @	INTAKE °	EXHAUST °	CLOSES °	ADVERTISED DURATION
TAPPET LIFT	INTAKE °	EXHAUST °	CLOSES °	292°
				292°
PART NUMBER		RECOMMENDED RPM RANGE WITH MATCHING COMPONENTS		
LOADS: CLOSED	TRIPLE	DUAL	OUTER	INNER
OPEN				
	LBS.	@		OR
	LBS.	@		
CAM TIMING @ .050	OPENS	CLOSES	MAX LIFT	DURATION
TAPPET LIFT	INTAKE 8° BTDC	46° ABDC	109° ATDC	234°
	EXHAUST 56° BBDC	-2° BTDC	119° BTDC	234°

REMARKS:

200006